



ENGINEERED TO HANDLE THE LOAD.

A clean industrial presentation with a strong product-first hierarchy.

DIMENSIONS + CAPACITY

MODEL	RT1235-80
GVWR	3,500 lbs.
EMPTY WEIGHT	1,150 lbs.
CARRYING CAPACITY	2,750 lbs.
OVERALL LENGTH	11 ft. 5 in.
OVERALL WIDTH	89 in.
OVERALL HEIGHT	67 in.
MAX REEL DIAMETER	80 in.
MIN REEL WIDTH	60 in.

RUNNING GEAR + FRAME

BRAKES	Electric Brakes - Optional
TIRES	ST205/75R14 LRD
WHEELS	14 x 6, 5 Bolt Mod
MAIN FRAME	4 in. x 2 in. x 3/16 in. Tubing
TONGUE	Adjustable Pintle Eye
FENDERS	12 ga.

ELECTRICAL + SAFETY

PLUG	7 RV Molded Plug
WIRING	Enclosed in Tube with Junction Box
LIGHTS	Protected Standard LED
CHAINS	5/16 in. with Slip Hook & Safety Latch
BREAKAWAY	Battery, Battery Box and Switch - Optional
DECALS	Warning Decals and Reflective Tape
FINISH	Industrial Urethane Yellow

INCLUDED ACCESSORIES

TOOLBOX