



MODEL: CT2786R-LT

SPECIFICATIONS

DESCRIPTION

MODEL – CT2786R-LT

GVWR – 9,850 lbs.

Empty Weight – 5,300 lbs.

Carrying Capacity – 4,550 lbs.

Overall Length – 27 ft.

Overall Width – 96 in.

Overall Height without Reel – 7 ft. – 9 in.

Overall Height with 125 in. Reel – 12 ft. – 8 in.

Maximum Reel OD – 125 in.

Maximum Reel Width – 62 in.

Side Loading

Lift Reel Only 3 ft. to Load

RUNNING GEAR

Dual Axle – 5,200 lbs. Each

Brakes – Electric

Tires – ST225/75R15 LRD

Wheels – 15 x 6 6 Bolt Mod

Suspension – Slipper Leaf Spring

FRAME

Main Frame – Double Frame – 8 x 2 x 3/16"
Tube / 6 x 4 x 3/16" Tube

Coil Cage – 2 x 2 x 1/4" Square Tube

Threading Rollers – 3 1/2" Sch 40 Pipe

Tongue – 6 x 4 x 3/16" Tube with Pintle Eye

Fenders – 12 ga.

Adjustable Height for Different Size Reels

ELECTRICAL

Plug – 7 RV Molded Plug

Wiring – Enclosed in Tube with Junction Box

Lights – Standard LED

SAFETY

Chains – 3/8 with Heavy Duty Hook & Safety Latch

Breakaway – Battery, Battery Box and Switch

Decals – Warning Decals and Reflective Tape

INCLUDED ACCESSORIES

McElroy 4-6 in. LineTamer® (LT0048)

FINISH

Sherwin-Williams Paint

Industrial Urethane Yellow

HYDRAULICS

Motor – 5.5 HP Honda Motor

Valve – 2 Spool Valve

Threading Roller Cylinder – 2 1/2 x 6 in. Tie Rod

AVAILABLE OPTIONS

Optional McElroy 2" LineTamer® (LT0122)

Optional 2" LineTamer® Mount 9 (LTM1)

Optional 3" Re-Round Kit (LT0037)

