



MODEL: HRT1286

SPECIFICATIONS

DESCRIPTION

MODEL – HRT1286
GVWR – 9,850 lbs.
Empty Weight – 3,800 lbs.
Carrying Capacity – 6,050 lbs.
Overall Length – 19 ft. – 2 in.
Overall Width – 96 in.
Overall Height – 118 in.
Reel Size Max OD – 125 in.
Reel Size Max Width – 65 in.

RUNNING GEAR

Dual Axle – 5,200 lbs. Each
Brakes – Electric
Tires – ST225/75R15 LRD
Wheels – 15 x 6 6 Bolt Mod
Suspension – Slipper Leaf Spring

FRAME

Main Frame – Double Frame – 8 x 2 x 3/16" Tube
/ 6 x 4 x 3/16" Tube
Coil Cage – 1 1/2 x 1 1/2 x 1/8" Square Tube &
Expandable Metal
Threading Rollers – 3 1/2" Sch 40 Pipe
Tongue – 6 x 4 x 3/16" Tube with Pintle Eye
Fenders – 12 ga.

ELECTRICAL

Plug – 7 RV Molded Plug
Wiring – Enclosed in Tube with Junction Box
Lights – Standard LED

SAFETY

Chains – 3/8" with Heavy Duty Hook & Safety Latch
Breakaway – Battery, Battery Box and Switch
Decals – Warning Decals and Reflective Tape

FINISH

Industrial Urethane Yellow

HYDRAULICS

Motor – 5.5 HP Honda Motor
Valve – 2 Spool Valve
Threading Roller Cylinder – 2 1/2 x 6 in. Tie Rod
Lifting Roller Cylinder – 4 x 36 in. Tie Rod

AVAILABLE OPTIONS

Frequently bought along with Pup Trailer (**TL1028**)



**Pup Trailer
(TL1028)**

