



MODEL: CT2786R-LT

SPECIFICATIONS

DESCRIPTION

MODEL – CT2786R-LT
GVWR – 9,850 lbs.
Empty Weight – 5,300 lbs.
Carrying Capacity – 4,550 lbs.
Overall Length – 27 ft.
Overall Width – 96 in.
Overall Height without Reel – 7 ft. – 9 in.
Overall Height with 125 in. Reel – 12 ft. – 8 in.
Maximum Reel OD – 125 in.
Maximum Reel Width – 62 in.
Side Loading
Lift Reel Only 3 ft. to Load

RUNNING GEAR

Dual Axle – 5,200 lbs. Each
Brakes – Electric
Tires – ST225/75R15 LRD
Wheels – 15 x 6 6 Bolt Mod
Suspension – Slipper Leaf Spring

FRAME

Main Frame – Double Frame – 8 x 2 x 3/16"
Tube / 6 x 4 x 3/16" Tube
Coil Cage – 2 x 2 x 1/4" Square Tube
Threading Rollers – 3 1/2" Sch 40 Pipe
Tongue – 6 x 4 x 3/16" Tube with Pintle Eye
Fenders – 12 ga.
Adjustable Height for Different Size Reels

ELECTRICAL

Plug – 7 RV Molded Plug
Wiring – Enclosed in Tube with Junction Box
Lights – Standard LED

SAFETY

Chains – 3/8 with Heavy Duty Hook & Safety Latch
Breakaway – Battery, Battery Box and Switch
Decals – Warning Decals and Reflective Tape

INCLUDED ACCESSORIES

McElroy 4-6 in. LineTamer® (LT0048)
Toolbox – Black Aluminum Diamond Plate

FINISH

Polyurethane Enamel

HYDRAULICS

Motor – 5.5 HP Honda Motor
Valve – 2 Spool Valve
Threading Roller Cylinder – 2 1/2 x 6 in. Tie Rod

AVAILABLE OPTIONS

Optional McElroy 2" LineTamer® (LT0122)
Optional 2" LineTamer® Mount (LTM2)
Optional 3" Re-Round Kit (LT0037)

